

according to Regulation (EC) No. 1907/2006 as amended by (EC) No. 1272/2008

Section 1. Identification of the Substance/Mixture and of the Company/Undertaking

- 1.1 Product Code:** C33V
Product Name: Silicone Spray
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
- 1.3 Details of the Supplier of the Safety Data Sheet:**
- | | | | |
|--------------------------|---|----------------------|---------------|
| Company Name: | CYCLO INDUSTRIES, INC.
902 SOUTH US HIGHWAY 1
JUPITER, FL 33477 | Phone Number: | (800)843-7813 |
| Web site address: | www.cyclo.com | | |
| Information: | First Aid Emergency (Outside U.S.) | | (312)906-6194 |
- 1.4 Emergency telephone number:**
- | | | |
|---------------------------|-------------------------|---------------|
| Emergency Contact: | First Aid Emergency | (800)752-7869 |
| | CHEMTREC (703) 527-3887 | (800)424-9300 |

Section 2. Hazards Identification

- 2.1 Classification of the Substance or Mixture:**
- 2.1.1 Classification according to Regulation (EC) No 1272/2008 [CLP]:**
Flammable Liquids, Category 1
Skin Corrosion/Irritation, Category 2
Target Organ Systemic Toxicity (single exposure), Category 3
Aspiration Toxicity, Category 1
Aquatic Toxicity (Acute), Category 1
Aquatic Toxicity (Chronic), Category 1
- 2.1.2 Classification according to Directive 1999/45/EC:**
- 2.2 Label Elements:**
- 2.2.1 Labeling according to Regulation (EC) No 1272/2008 [CLP]:**

**GHS Signal Word:** Danger**GHS Hazard Phrases:**

H224: Extremely flammable liquid and vapor.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H304: May be fatal if swallowed and enters airways.

H410: Very toxic to aquatic life with long lasting effects. H280: Contents under pressure. May explode if heated.

GHS Precaution Phrases:

P233: Keep container tightly closed.

P210: Keep away from heat/sparks/open flames/hot surfaces.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P243: Take precautionary measures against static discharge.

P242: Use only non-sparking tools.

P264: Wash hands thoroughly after handling.

P362+364: Take off contaminated clothing and wash it before reuse.

P271: Use only outdoors or in a well-ventilated area.



SAFETY DATA SHEET

Silicone Spray

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P273: Avoid release to the environment.

GHS Response Phrases:

P370+378: In case of fire, use foam, CO₂, dry chemical or water fog to extinguish.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331: Do NOT induce vomiting.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P332+313: If skin irritation occurs, get medical advice/attention.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists, get medical advice/attention.

P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

GHS Storage and Disposal Phrases:

P403+233: Store container tightly closed in well-ventilated place.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

2.2.2 Labeling according to Directive 1999/45/EC:

Hazard Rating System:

HEALTH	1
FLAMMABILITY	4
REACTIVITY	0
PPE	

2.3 Adverse Human Health

Effects and Symptoms:

Medical Conditions None known when used as directed.

Generally Aggravated

By Exposure:

Section 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)/ REACH Registration No.	Concentration	EC No./ EC Index No.	Risk Phrases/ GHS Classification
64742-47-8	Hydrotreated light distillate (petroleum)	32.0 %	265-149-8 649-422-00-2	Xn; R65 Asp. Toxic. 1: H304
142-82-5	Heptane	30.0 %	205-563-8 601-008-00-2	F; Xn; N; R11-38-50/53-65-67 Flam. Liq. 2: H225 Asp. Toxic. 1: H304 Skin Corr. 2: H315 TOST (SE) 3: H335 H336 Aquatic (A) 1: H400 Aquatic (C) 1: H410
74-98-6	Propane	30.0 %	200-827-9 601-003-00-5	F+; R12 Comp. Gas: H280 Flam. Gas 1: H220



Section 4. First Aid Measures

- 4.1 Description of First Aid Measures:** If swallowed, induce vomiting only on the advice of a physician. If inhaled, remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. In case of skin contact, wipe off with towel. Wash area with soap and water. In case of eye contact, flush with water for at least 15 minutes. Call physician immediately if adverse reaction occurs.

Section 5. Fire Fighting Measures

- 5.1 Suitable Extinguishing Media:** Foam, CO2, dry chemical, water fog.
- 5.2 Flammable Properties and Hazards:** Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Vapor accumulation can flash or explode if ignited. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention.
- Flash Pt:** NE -156.00 F (-104.4 C) Method Used: Estimate
- Explosive Limits:** LEL: .7 UEL: 9.5
- Autoignition Pt:** No data.
- 5.3 Fire Fighting Instructions:** Wear goggles and self-contained breathing apparatus. Water spray may be ineffective. Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. If water is used, fog nozzles preferred.

Section 6. Accidental Release Measures

- 6.3 Methods and Material For Containment and Cleaning Up:** Avoid breathing vapors. Ventilate area. Remove all sources of ignition. Clean up area with absorbent material and place in closed containers for disposal.

Section 7. Handling and Storage

- 7.1 Precautions To Be Taken in Handling:** Do not puncture or incinerate cans. Do not stick pin, nail or any other sharp object into opening on top of can. Do not spray in eyes. Keep out of the reach of children.
- 7.2 Precautions To Be Taken in Storing:** Store and use in cool, dry, well-ventilated areas. Vapors may cause flash fire. Keep away from heat, sparks and flame. Do not store above 120 degrees F.

Section 8. Exposure Controls/Personal Protection

8.1 Exposure Parameters:

CAS #	Partial Chemical Name	Britain EH40	France VL	Europe
64742-47-8	Hydrotreated light distillate (petroleum)	No data.	No data.	No data.
142-82-5	Heptane	TWA: 2085 mg/m3 (500 ppm) STEL: ()	TWA: 1668 mg/m3 (400 ppm) STEL: 2085 mg/m3 (500 ppm)	TWA: 2085. mg/m3
74-98-6	Propane	No data.	No data.	No data.
CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light distillate (petroleum)	PEL: 1000 ppm	TLV: 200 mg/m3	No data.
142-82-5	Heptane	PEL: 500 ppm	TLV: 400 ppm	No data.
74-98-6	Propane	PEL: 1000 ppm	TLV: (2500 ppm)	No data.



8.2 Exposure Controls:

8.2.1 Engineering Controls (Ventilation etc.): Sufficient to prevent inhalation of solvent vapors. General dilution and/or local exhaust ventilation in volume or pattern to keep PEL/TLV of most hazardous ingredient below acceptable limit and LEL below stated limit.

8.2.2 Personal protection equipment:

Eye Protection: Use of safety glasses with splash guards or full face shield is recommended.

Protective Gloves: Solvent resistant gloves required for prolonged or repeated contact.

Other Protective Clothing: Use of solvent resistant aprons or other clothing is recommended.

Respiratory Equipment (Specify Type): Avoid breathing vapors. Use with adequate ventilation equal to out of doors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use approved air line type respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Work/Hygienic/Maintenance Practices: Eye washes and safety showers in the workplace are recommended.

Section 9. Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Concentrate is clear liquid.

Melting Point: No data.

Boiling Point: -44.00 F (-42.2 C) - -410.00 F (-245.6 C)

Flash Pt: NE -156.00 F (-104.4 C) Method Used: Estimate

Evaporation Rate: No data.

Explosive Limits: LEL: .7 UEL: 9.5

Vapor Pressure (vs. Air or mm Hg): No data.

Vapor Density (vs. Air = 1): > air

Specific Gravity (Water = 1): .64

Solubility in Water: No data.

Autoignition Pt: No data.

9.2 Other Information

Percent Volatile: 60.0 % by weight.

Section 10. Stability and Reactivity

10.1 Reactivity: No data available.

10.2 Stability: Unstable [] Stable [X]

10.3 Conditions To Avoid - Hazardous Reactions: No data available.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

10.4 Conditions To Avoid - Instability: Application to hot surfaces. Storage above 120 degrees F. Exposure to open flame.

10.5 Incompatibility - Materials To Avoid: Strong oxidizing agents.

10.6 Hazardous Decomposition Or Byproducts: Fumes may contain carbon monoxide and other toxic fumes.

Section 11. Toxicological Information

11.1 Information on Toxicological Effects:

No data available.

CAS# 142-82-5:

Other Studies:, TDLo, Oral, Rat, 60.00 GM/KG, 3 W.

Results:

Kidney, Ureter, Bladder: Changes in liver weight.

- National Technical Information Service, Vol/p/yr: OTS0571116,

Other Studies:, TDLo, Oral, Rat, 260.0 GM/KG, 13 W.

Results:

Kidney, Ureter, Bladder: Changes in bladder weight.

Endocrine:Hypoglycemia.

Nutritional and Gross Metabolic:Weight loss or decreased weight gain.

- National Technical Information Service, Vol/p/yr: OTS0571116,

Other Studies:, TCLo, Inhalation, Rat, 4000. PPM, 6 D.

Results:

Brain and Coverings: Recordings from specific areas of CNS.

Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Ear: Changes in cochlear structure or function.

Nutritional and Gross Metabolic:Weight loss or decreased weight gain.

- Pharmacology and Toxicology, Munksgaard International Pub., POB 2148, Copenhagen K Denmark, Vol/p/yr: 76,41, 1995

Other Studies:, TDLo, Intraperitoneal, Rat, 9625. MG/KG, 7 D.

Results:

Liver: Other changes.

Blood:Changes in serum composition (e.g.

Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels: Multiple enzyme effects.

- Toxicology Letters., Elsevier Science Pub. B.V., POB 211, 1000 AE, Amsterdam 1000 AE Netherlands, Vol/p/yr: 14,169, 1982

Other Studies:, TDLo, Intraperitoneal, Rat, 8840. MG/KG, 45 D.

Results:

Liver: Other changes.

Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels:

Phosphatases.

Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels: Hepatic microsomal mixed oxidase (dealkylation, hydroxylation, etc.)

- JAT, Journal of Applied Toxicology., John Wiley & Sons Ltd., Baffins Lane, Chichester, W.Sussex PO19 1UD UK, Vol/p/yr: 8,81, 1988

Acute toxicity, TCLo, Inhalation, Human, 1000. PPM, 6 M.

Results:

Behavioral: Hallucinations, distorted perceptions.

- "U.S. Bureau of Mines Report of Investigation No. 2979," Patty, F.A., and W.P. Yant, 1929 Volume, Vol/p/yr: 2979,-, 1929

Acute toxicity, LC50, Inhalation, Rat, 103.0 GM/M3, 4 H.

Results:



SAFETY DATA SHEET

Silicone Spray

Behavioral: Change in motor activity (specific assay).

Behavioral: Alteration of classical conditioning.

- Gigiena Truda i Professional'nye Zabolevaniya. (Labor Hygiene and Occupational Disease), V/O Mezhdunarodnaya Kniga, Moscow 113095 Russia, Vol/p/yr: 32(10),23, 1988

Acute toxicity, LCLO, Inhalation, Mouse, 59.00 GM/M3, 41 M.

Results:

Behavioral: Convulsions or effect on seizure threshold.

- Biochemische Zeitschrift., For publisher information, see EJBCAI, Berlin Germany, Vol/p/yr: 115,235, 1921

Acute toxicity, LD50, Intravenous, Mouse, 222.0 MG/KG.

Results:

Brain and Coverings: Changes in circulation (hemorrhage, thrombosis, etc.

Lungs, Thorax, or Respiration: Dyspnea.

Gastrointestinal: Nausea or vomiting.

- Journal of Pharmaceutical Sciences., American Pharmaceutical Assoc., 2215 Constitution Ave., NW, Washington, DC 20037, Vol/p/yr: 67,566, 1978

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum)	n.a.	n.a.	A4	n.a.
142-82-5	Heptane	n.a.	n.a.	n.a.	n.a.
74-98-6	Propane	n.a.	n.a.	n.a.	n.a.

Section 12. Ecological Information

12.1 Toxicity:

CAS# 142-82-5:

Effective concentration to 50% of test organisms., Water Flea (*Daphnia magna*), 82500. UG/L, 96 H, Intoxication., Water temperature: 28.00 C (82.4 F) C.

Results:

No observed effect.

- Acute Toxicity of Petroleum Products, Crude Oil and Oil Refinery Effluent on Plankton, Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

LC50, Water Flea (*Daphnia magna*), 50.00 MG/L, 24 H, Intoxication., Water temperature: 20.00 C (68.0 F) - 22.00 C (71.6 F) C, pH: 7.70, Hardness: 16.00 dH.

Results:

No observed effect.

- Results of the Damaging Effect of Water Pollutants on *Daphnia magna* (Befunde der Schädigung Wassergefährdender Stoffe Gegen *Daphnia magna*), Bringmann, G., and R. Kuhn, 1977

LC50, Western Mosquitofish (*Gambusia affinis*), adult(s), 4924000. UG/L, 48 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.

Results:

Age Effects.

- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

LC50, Western Mosquitofish (*Gambusia affinis*), adult(s), 4924000. UG/L, 24 H, Mortality,



SAFETY DATA SHEET

Silicone Spray

Page: 7

Revision: 04/01/2014

Supersedes Revision: 12/13/2013

Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.

Results:

Age Effects.

- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

Not reported., Western Mosquitofish (*Gambusia affinis*), adult(s), 5600000. UG/L, 96 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.

Results:

No observed effect.

- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

LC50, Western Mosquitofish (*Gambusia affinis*), adult(s), 4924000. UG/L, 96 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.

Results:

No observed effect.

- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

Not reported., Coho Salmon, Silver Salmon (*Oncorhynchus kisutch*), 100000. UG/L, 96 H, Mortality, Water temperature: 8.00 C (46.4 F) C, pH: 8.10.

Results:

Age Effects.

- Effects of Some Components of Crude Oil on Young Coho Salmon, Morrow, J.E., R.L. Gritz, and M.P. Kirton, 1975

LC50, Mozambique Tilapia (*Oreochromis mossambicus*), 375000. UG/L, 96 H, Mortality, Water temperature: 27.80 C (82.0 F) C.

Results:

No observed effect.

- Acute Toxicity of n-Heptane and n-Hexane on Worm and Fish, Ghatak, D.B., M.M. Hossain, and S.K. Konar, 1988

LC50, Midge Family (Chironomidae), larva(e), 838000. UG/L, 96 H, Intoxication,, Water temperature: 28.00 C (82.4 F) C, pH: 7.00, Hardness: 260.00 MG/L.

Results:

No observed effect.

- Acute Toxicity of Petroleum Products, Crude Oil and Oil Refinery Effluent on Plankton, Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

Effective concentration to 50% of test organisms., Algae (Algae), 1500. UG/L, 8 H, Physiology.

Results:

No observed effect.

- Gulf Underwater Flare Experiment (GUFEX): Effects of Hydrocarbons on Phytoplankton, Brooks, J.M., G.A. Fryxell, D.F. Reid, and W.M. Sackett, 1977

Not reported., Pacific Oyster (*Crassostrea gigas*), egg(s), 3400000. UG/L, 48 H, Mortality, Water temperature: 20.00 C (68.0 F) - 21.50 C (70.7 F) C.

Results:

No observed effect.

- The Effect of Alaskan Crude Oil and Selected Hydrocarbon Compounds on Embryonic

Development of the Pacific Oyster, *Crassostrea gigas*, Legore, R.S., 1974

LC50, Oligochaete (*Branchiura sowerbyi*), 2500000. UG/L, 96 H, Mortality, Water temperature: 27.80 C (82.0 F) C.

Results:

No observed effect.

- Acute Toxicity of n-Heptane and n-Hexane on Worm and Fish, Ghatak, D.B., M.M.

Hossain, and S.K. Konar, 1988

Effective concentration to 50% of test organisms., Snail (*Viviparus bengalensis*), 472000. UG/L, 96 H, Intoxication,, Water temperature: 28.00 C (82.4 F) C.

Results:

No observed effect.

- Acute Toxicity of Petroleum Products, Crude Oil and Oil Refinery Effluent on Plankton,

Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

Lethal concentration to 0% of test organisms., Carp (*Leuciscus idus ssp. melanotus*), 220.0 MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

LC50, Carp (*Leuciscus idus ssp. melanotus*), 270.0 MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Lethal concentration to 100% of test organisms., Carp (*Leuciscus idus ssp. melanotus*), 350.0 MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Lethal concentration to 0% of test organisms., Carp (*Leuciscus idus ssp. melanotus*), 1370. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

LC50, Carp (*Leuciscus idus ssp. melanotus*), 2940. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978



Lethal concentration to 100% of test organisms., Carp (*Leuciscus idus ssp. melanotus*), 3420. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Section 13. Disposal Considerations

13.1 Waste Disposal Method: Disposal should be made in accordance with federal, state and local regulations.

Section 14. Transport Information

14.1 LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Consumer Commodity
DOT Hazard Class: ORM-D ORM-D
UN/NA Number:

14.1 LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name: Aerosols, 2.1, Ltd. Qty
UN Number: 1950
Hazard Class: N.A. **ADR Classification:** 2.1

14.2 MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Aerosols, 2.1, Ltd. Qty
UN Number: 1950 **Packing Group:**
Hazard Class: N.A. **IMDG Classification:** 2.1

14.3 AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Aerosols, flammable, 2.1, Ltd Qty
UN Number: 1950
Hazard Class: N.A. **IATA Classification:** 2.1

Section 15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-47-8	Hydrotreated light distillate (petroleum)	No	No	No
142-82-5	Heptane	No	No	No
74-98-6	Propane	No	No	No

CAS # Hazardous Components (Chemical Name)

Other US EPA or State Lists

64742-47-8	Hydrotreated light distillate (petroleum)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
142-82-5	Heptane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Inventory, 4 Test, 8A PAIR; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 1339; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No
74-98-6	Propane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 1594; NY Part



SAFETY DATA SHEET

Silicone Spray

Revision: 04/01/2014

Supersedes Revision: 12/13/2013

597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No

CAS #	Hazardous Components (Chemical Name)
64742-47-8	Hydrotreated light distillate (petroleum)
142-82-5	Heptane
74-98-6	Propane

International Regulatory Lists

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

European Community Hazard Symbol codes:

European Community Risk and Safety Phrases:

No data available.

Section 16. Other Information

Revision Date: 04/01/2014**Additional Information About** No data available.**This Product:****Company Policy or****Disclaimer:**

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.