


according to Regulation (EC) No. 1907/2006 as amended by (EC) No. 1272/2008

**Section 1. Identification of the Substance/Mixture and of the Company/Undertaking**

- 1.1 Product Code:** C36  
**Product Name:** Disc Brake Quiet
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
- 1.3 Details of the Supplier of the Safety Data Sheet:**
- |                          |   |                      |               |
|--------------------------|---|----------------------|---------------|
| <b>Company Name:</b>     | CYCLO INDUSTRIES, INC.<br>902 SOUTH US HIGHWAY 1<br>JUPITER, FL 33477 | <b>Phone Number:</b> | (800)843-7813 |
| <b>Web site address:</b> | www.cyclo.com   |                      |               |
| <b>Information:</b>      | First Aid Emergency (Outside U.S.)                                    |                      | (312)906-6194 |
- 1.4 Emergency telephone number:**
- |                           |                         |               |
|---------------------------|-------------------------|---------------|
| <b>Emergency Contact:</b> | First Aid Emergency     | (800)752-7869 |
|                           | CHEMTREC (703) 527-3887 | (800)424-9300 |

**Section 2. Hazards Identification**

- 2.1 Classification of the Substance or Mixture:**
- 2.1.1 Classification according to Regulation (EC) No 1272/2008 [CLP]:**  
Flammable Gases, Category 1  
Gas Under Pressure, Compressed gas  
Flammable Liquids, Category 2  
Skin Corrosion/Irritation, Category 2  
Toxic To Reproduction, Category 2  
Target Organ Systemic Toxicity (single exposure), Category 3  
Target Organ Systemic Toxicity (repeated exposure), Category 2  
Aspiration Toxicity, Category 1
- 2.1.2 Classification according to Directive 1999/45/EC:**
- 2.2 Label Elements:**
- 2.2.1 Labeling according to Regulation (EC) No 1272/2008 [CLP]:**

**GHS Signal Word:** Danger**GHS Hazard Phrases:**

H220: Extremely flammable gas.  
H225: Highly flammable liquid and vapor.  
H315: Causes skin irritation.  
H361: Suspected of damaging fertility or the unborn child.  
H335: May cause respiratory irritation.  
H373: May cause damage to organs through prolonged or repeated exposure.  
H304: May be fatal if swallowed and enters airways.  
H280: Contents under pressure. May explode if heated.

**GHS Precaution Phrases:**

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.  
P280: Wear protective gloves/clothing and eye/face protection.  
P240: Ground/bond container and receiving equipment.  
P241: Use explosion-proof electrical/ventilating/lighting equipment.  
P264: Wash hands thoroughly after handling.  
P271: Use only outdoors or in a well-ventilated area.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P273: Avoid release to the environment.

### GHS Response Phrases:

P370+378: In case of fire, use CO<sub>2</sub>, dry chemical or foam for extinction.

P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P363: Wash contaminated clothing before reuse.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

### GHS Storage and Disposal Phrases:


P410: Protect from sunlight.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

P403+233: Store container tightly closed in well-ventilated place.

## 2.2.2 Labeling according to Directive 1999/45/EC:

### Hazard Rating System:



## 2.3 Adverse Human Health Effects and Symptoms:

# Section 3. Composition/Information on Ingredients

Section 3. Composition/Information on Ingredients				
CAS #	Hazardous Components (Chemical Name)/ REACH Registration No.	Concentration	EC No./ EC Index No.	Risk Phrases/ GHS Classification
142-82-5	Heptane	40.0 -50.0 %	205-563-8 601-008-00-2	F; Xn; N; R11-38-50/53-65-67 Flam. Liq. 2: H225 Asp. Toxic. 1: H304 Skin Corr. 2: H315 TOST (SE) 3: H335 H336 Aquatic (A) 1: H400 Aquatic (C) 1: H410
74-98-6	Propane	10.0 -20.0 %	200-827-9 601-003-00-5	F+; R12 Comp. Gas: H280 Flam. Gas 1: H220
108-88-3	Toluene	10.0 -15.0 %	203-625-9 601-021-00-3	F; Xn; R11-38-48/20-63-65-67 Flam. Liq. 2: H225 Asp. Toxic. 1: H304 Skin Corr. 2: H315 TOST (SE) 3: H335 H336 Toxic Repro. 2: H361 TOST (RE) 2: H373
106-97-8	Butane	1.0 -10.0 %	203-448-7 601-004-01-8	F+; T; R45-46-12 Flam. Gas 1: H220 Comp. Gas: H280

### Section 4. First Aid Measures

**4.1 Description of First Aid Measures:** If swallowed, seek medical attention immediately. Aspiration hazard: do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Do not leave individual unattended. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of skin contact, wash with soap and water. Remove contaminated clothing and shoes, and launder before reuse. Call physician immediately if adverse reaction occurs.

### Section 5. Fire Fighting Measures

**5.1 Suitable Extinguishing Media:** Carbon dioxide, dry chemicals, foam.

**5.2 Flammable Properties and Hazards:** No data available.

**Flammability Classification:** NFPA Level 2 Aerosol

**Flash Pt:** <= 0.00 F (-17.8 C) Method Used: TAG Closed Cup

**Explosive Limits:** LEL: No data. UEL: No data.

**Autoignition Pt:** No data.

**5.3 Fire Fighting Instructions:** EXTREMELY FLAMMABLE. Contents under pressure. Cool exposed containers with water spray to prevent bursting. SCBA should be used whenever chemical fires are present.

### Section 6. Accidental Release Measures

**6.3 Methods and Material For Containment and Cleaning Up:** Wear appropriate protective clothing and equipment to prevent skin and eye contact. Contain any liquid from leaking containers. Remove sources of ignition. Increase area ventilation. Do not puncture or incinerate container. Contents under pressure. Clean up using dry procedures; avoid dusting. Sweep or gather up material and place in proper container for disposal or recovery. Do not allow to enter sanitary drains, sewer or surface and subsurface waters.

### Section 7. Handling and Storage

**7.1 Precautions To Be Taken in Handling:** Keep away from heat/sparks/open flames/hot surfaces - No smoking. Wear protective gloves/clothing and eye/face protection. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid release to the environment. Keep out of the reach of children.

**7.2 Precautions To Be Taken in Storing:** Store container tightly closed in well-ventilated place. Protect from sunlight.

### Section 8. Exposure Controls/Personal Protection

**8.1 Exposure Parameters:**

CAS #	Partial Chemical Name	Britain EH40	France VL	Europe
142-82-5	Heptane	TWA: 2085 mg/m3 (500 ppm) STEL: ()	TWA: 1668 mg/m3 (400 ppm) STEL: 2085 mg/m3 (500 ppm)	TWA: 2085. mg/m3
74-98-6	Propane	No data.	No data.	No data.



# SAFETY DATA SHEET

## Disc Brake Quiet

Revision: 10/02/2014  
Supersedes Revision: 05/07/2014

108-88-3	Toluene	TWA: 191 mg/m3 (50 ppm) STEL: 384 mg/m3 (100 ppm)	TWA: 192 mg/m3 (50 ppm) STEL: 384 mg/m3 (100 ppm)	TWA: 192 mg/m3 STEL: 384 mg/m3
106-97-8	Butane	TWA: 1450 mg/m3 (600 ppm) STEL: 1810 mg/m3 (750 ppm)	TWA: 1900 mg/m3 (800 ppm)	No data.
<b>CAS #</b>	<b>Partial Chemical Name</b>	<b>OSHA TWA</b>	<b>ACGIH TWA</b>	<b>Other Limits</b>
142-82-5	Heptane	PEL: 500 ppm	TLV: 400 ppm	No data.
74-98-6	Propane	PEL: 1000 ppm	TLV: (2500 ppm)	No data.
108-88-3	Toluene	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	TLV: 50 ppm	No data.
106-97-8	Butane	No data.	TLV: (800 ppm)	No data.

### 8.2 Exposure Controls:

**8.2.1 Engineering Controls (Ventilation etc.):** Exhaust ventilation. Showers. Eyewash stations.

### 8.2.2 Personal protection equipment:

**Eye Protection:** Wear safety glasses or goggles to protect against exposure.

**Protective Gloves:** Use chemical resistant gloves for prolonged skin contact.

**Other Protective Clothing:** Rubber apron.

**Respiratory Equipment (Specify Type):** Use an approved NIOSH organic vapor respirator below the TLV. If TLV is exceeded or overexposure is likely, use positive pressure or self-contained breathing apparatus.

## Section 9. Physical and Chemical Properties

### 9.1 Information on Basic Physical and Chemical Properties

<b>Physical States:</b>	[ ] Gas [ X ] Liquid [ ] Solid
<b>Appearance and Odor:</b>	Clear, colorless spray/mist. Typical solvent odor.
<b>Melting Point:</b>	NE
<b>Boiling Point:</b>	No data.
<b>Flash Pt:</b>	<= 0.00 F (-17.8 C) Method Used: TAG Closed Cup
<b>Evaporation Rate:</b>	NE
<b>Explosive Limits:</b>	LEL: No data. UEL: No data.
<b>Vapor Pressure (vs. Air or mm Hg):</b>	NE
<b>Vapor Density (vs. Air = 1):</b>	NE
<b>Specific Gravity (Water = 1):</b>	.81
<b>Solubility in Water:</b>	Negligible
<b>Autoignition Pt:</b>	No data.
<b>Viscosity:</b>	NE



**9.2 Other Information**

**Percent Volatile:** 88.5 % by weight.

**Section 10. Stability and Reactivity**

- 10.1 Reactivity:** No data available.
- 10.2 Stability:** Unstable [ ] Stable [ X ]
- 10.3 Conditions To Avoid - Hazardous Reactions:** No data available.
- Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [ X ]
- 10.4 Conditions To Avoid - Instability:** Keep away from heat, sparks and flame. Temperature over 120 degrees F.
- 10.5 Incompatibility - Materials To Avoid:** Strong acids. Strong oxidizing agents.
- 10.6 Hazardous Decomposition Or Byproducts:** Carbon monoxide. Carbon dioxide.

**Section 11. Toxicological Information**

- 11.1 Information on Toxicological Effects:** No data available.
- CAS# 142-82-5:  
Other Studies:, TDLo, Oral, Rat, 60.00 GM/KG, 3 W.  
Results:  
Kidney, Ureter, Bladder: Changes in liver weight.  
- National Technical Information Service, Vol/p/yr: OTS0571116,
- Other Studies:, TDLo, Oral, Rat, 260.0 GM/KG, 13 W.  
Results:  
Kidney, Ureter, Bladder: Changes in bladder weight.  
Endocrine:Hypoglycemia.  
Nutritional and Gross Metabolic:Weight loss or decreased weight gain.  
- National Technical Information Service, Vol/p/yr: OTS0571116,
- Other Studies:, TCLo, Inhalation, Rat, 4000. PPM, 6 D.  
Results:  
Brain and Coverings: Recordings from specific areas of CNS.  
Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Ear: Changes in cochlear structure or function.  
Nutritional and Gross Metabolic:Weight loss or decreased weight gain.  
- Pharmacology and Toxicology, Munksgaard International Pub., POB 2148, Copenhagen K Denmark, Vol/p/yr: 76,41, 1995
- Other Studies:, TDLo, Intraperitoneal, Rat, 9625. MG/KG, 7 D.  
Results:  
Liver: Other changes.  
Blood:Changes in serum composition (e.g.  
Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels: Multiple enzyme effects.  
- Toxicology Letters., Elsevier Science Pub. B.V., POB 211, 1000 AE, Amsterdam 1000 AE Netherlands, Vol/p/yr: 14,169, 1982



# SAFETY DATA SHEET

## Disc Brake Quiet

Revision: 10/02/2014

Supersedes Revision: 05/07/2014

Other Studies:, TDLo, Intraperitoneal, Rat, 8840. MG/KG, 45 D.

Results:

Liver: Other changes.

Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels:

Phosphatases.

Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels: Hepatic microsomal mixed oxidase (dealkylation, hydroxylation, etc.)

- JAT, Journal of Applied Toxicology., John Wiley & Sons Ltd., Baffins Lane, Chichester, W.Sussex PO19 1UD UK, Vol/p/yr: 8,81, 1988

Acute toxicity, TCLO, Inhalation, Human, 1000. PPM, 6 M.

Results:

Behavioral: Hallucinations, distorted perceptions.

- "U.S. Bureau of Mines Report of Investigation No. 2979," Patty, F.A., and W.P. Yant, 1929 Volume, Vol/p/yr: 2979,-, 1929

Acute toxicity, LC50, Inhalation, Rat, 103.0 GM/M3, 4 H.

Results:

Behavioral: Change in motor activity (specific assay).

Behavioral: Alteration of classical conditioning.

- Gigiena Truda i Professional'nye Zabolevaniya.(Labor Hygiene and Occupational Disease), V/O Mezhdunarodnaya Kniga, Moscow 113095 Russia, Vol/p/yr: 32(10),23, 1988

Acute toxicity, LCLO, Inhalation, Mouse, 59.00 GM/M3, 41 M.

Results:

Behavioral: Convulsions or effect on seizure threshold.

- Biochemische Zeitschrift., For publisher information, see EJBCAI, Berlin Germany, Vol/p/yr: 115,235, 1921

Acute toxicity, LD50, Intravenous, Mouse, 222.0 MG/KG.

Results:

Brain and Coverings: Changes in circulation (hemorrhage,thrombosis, etc.

Lungs, Thorax, or Respiration:Dyspnea.

Gastrointestinal:Nausea or vomiting.

- Journal of Pharmaceutical Sciences., American Pharmaceutical Assoc., 2215 Constitution Ave., NW, Washington, DC 20037, Vol/p/yr: 67,566, 1978

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
142-82-5	Heptane	n.a.	n.a.	n.a.	n.a.
74-98-6	Propane	n.a.	n.a.	n.a.	n.a.
108-88-3	Toluene	n.a.	3	A4	n.a.
106-97-8	Butane	n.a.	n.a.	n.a.	n.a.

## Section 12. Ecological Information

**12.1 Toxicity:**

CAS# 142-82-5:  
Effective concentration to 50% of test organisms., Water Flea (*Daphnia magna*), 82500. UG/L, 96 H, Intoxication., Water temperature: 28.00 C (82.4 F) C.  
Results:  
No observed effect.  
- Acute Toxicity of Petroleum Products, Crude Oil and Oil Refinery Effluent on Plankton, Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

LC50, Water Flea (*Daphnia magna*), 50.00 MG/L, 24 H, Intoxication., Water temperature: 20.00 C (68.0 F) - 22.00 C (71.6 F) C, pH: 7.70, Hardness: 16.00 dH.  
Results:  
No observed effect.  
- Results of the Damaging Effect of Water Pollutants on *Daphnia magna* (Befunde der Schadwirkung Wassergefährdender Stoffe Gegen *Daphnia magna*), Bringmann, G., and R. Kuhn, 1977

LC50, Western Mosquitofish (*Gambusia affinis*), adult(s), 4924000. UG/L, 48 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.  
Results:  
Age Effects.  
- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

LC50, Western Mosquitofish (*Gambusia affinis*), adult(s), 4924000. UG/L, 24 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.  
Results:  
Age Effects.  
- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

Not reported., Western Mosquitofish (*Gambusia affinis*), adult(s), 5600000. UG/L, 96 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.  
Results:  
No observed effect.  
- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

LC50, Western Mosquitofish (*Gambusia affinis*), adult(s), 4924000. UG/L, 96 H, Mortality, Water temperature: 20.00 C (68.0 F) - 27.00 C (80.6 F) C, pH: 8.90.  
Results:  
No observed effect.  
- Toxicity to *Gambusia affinis* of Certain Pure Chemicals in Turbid Waters, Wallen, I.E., W.C. Greer, and R. Lasater, 1957

Not reported., Coho Salmon, Silver Salmon (*Oncorhynchus kisutch*), 100000. UG/L, 96 H, Mortality, Water temperature: 8.00 C (46.4 F) C, pH: 8.10.  
Results:  
Age Effects.  
- Effects of Some Components of Crude Oil on Young Coho Salmon, Morrow, J.E., R.L. Gritz, and M.P. Kirton, 1975

LC50, Mozambique Tilapia (*Oreochromis mossambicus*), 375000. UG/L, 96 H, Mortality, Water temperature: 27.80 C (82.0 F) C.

Results:

No observed effect.

- Acute Toxicity of n-Heptane and n-Hexane on Worm and Fish, Ghatak, D.B., M.M. Hossain, and S.K. Konar, 1988

LC50, Midge Family (Chironomidae), larva(e), 838000. UG/L, 96 H, Intoxication,, Water temperature: 28.00 C (82.4 F) C, pH: 7.00, Hardness: 260.00 MG/L.

Results:

No observed effect.

- Acute Toxicity of Petroleum Products, Crude Oil and Oil Refinery Effluent on Plankton, Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

Effective concentration to 50% of test organisms., Algae (Algae), 1500. UG/L, 8 H, Physiology.

Results:

No observed effect.

- Gulf Underwater Flare Experiment (GUFEX): Effects of Hydrocarbons on Phytoplankton, Brooks, J.M., G.A. Fryxell, D.F. Reid, and W.M. Sackett, 1977

Not reported., Pacific Oyster (*Crassostrea gigas*), egg(s), 3400000. UG/L, 48 H, Mortality, Water temperature: 20.00 C (68.0 F) - 21.50 C (70.7 F) C.

Results:

No observed effect.

- The Effect of Alaskan Crude Oil and Selected Hydrocarbon Compounds on Embryonic Development of the Pacific Oyster, *Crassostrea gigas*, Legore, R.S., 1974

LC50, Oligochaete (*Branchiura sowerbyi*), 2500000. UG/L, 96 H, Mortality, Water temperature: 27.80 C (82.0 F) C.

Results:

No observed effect.

- Acute Toxicity of n-Heptane and n-Hexane on Worm and Fish, Ghatak, D.B., M.M. Hossain, and S.K. Konar, 1988

Effective concentration to 50% of test organisms., Snail (*Viviparus bengalensis*), 472000. UG/L, 96 H, Intoxication,, Water temperature: 28.00 C (82.4 F) C.

Results:

No observed effect.

- Acute Toxicity of Petroleum Products, Crude Oil and Oil Refinery Effluent on Plankton, Benthic Invertebrates and Fish, Das, P.K.M.K., and S.K. Konar, 1988

Lethal concentration to 0% of test organisms., Carp (*Leuciscus idus ssp. melanotus*), 220.0 MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

LC50, Carp (*Leuciscus idus ssp. melanotus*), 270.0 MG/L, 48 H, Mortality.

Results:

No observed effect.



- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Lethal concentration to 100% of test organisms., Carp (*Leuciscus idus* ssp. *melanotus*), 350.0 MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Lethal concentration to 0% of test organisms., Carp (*Leuciscus idus* ssp. *melanotus*), 1370. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

LC50, Carp (*Leuciscus idus* ssp. *melanotus*), 2940. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

Lethal concentration to 100% of test organisms., Carp (*Leuciscus idus* ssp. *melanotus*), 3420. MG/L, 48 H, Mortality.

Results:

No observed effect.

- Results of the Investigation of 200 Chemical Compounds for Acute Fish Toxicity with the Golden Orfe Test (Ergebnisse der Untersuchung von 200 Chemischen Verbindungen auf Akute Fischtoxizität mit dem Goldorfentest), Juhnke, I., and D. Luedemann, 1978

### Section 13. Disposal Considerations

**13.1 Waste Disposal Method:** Dispose of contents/container in accordance with local/regional/national/international regulation.

### Section 14. Transport Information

#### 14.1 LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Consumer Commodity  
**DOT Hazard Class:** ORM-D ORM-D  
**UN/NA Number:**

#### 14.1 LAND TRANSPORT (European ADR/RID):

**ADR/RID Shipping Name:** Aerosols, Ltd. Qty.  
**UN Number:** 1950  
**Hazard Class:** N.A. **ADR Classification:** 2.1



# SAFETY DATA SHEET

## Disc Brake Quiet

**14.2 MARINE TRANSPORT (IMDG/IMO):**

<b>IMDG/IMO Shipping Name:</b>	Aerosols, Ltd. Qty.	<b>Packing Group:</b>	
<b>UN Number:</b>	1950	<b>IMDG Classification:</b>	2.1
<b>Hazard Class:</b>	N.A.		

**14.3 AIR TRANSPORT (ICAO/IATA):**

<b>ICAO/IATA Shipping Name:</b>	Aerosols, flammable, 2.1, Ltd. Qty.	<b>IATA Classification:</b>	2.1
<b>UN Number:</b>	1950		
<b>Hazard Class:</b>	N.A.		

### Section 15. Regulatory Information

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
142-82-5	Heptane	No	No	No
74-98-6	Propane	No	No	No
108-88-3	Toluene	No	Yes 1000 LB	Yes
106-97-8	Butane	No	No	No

**CAS # Hazardous Components (Chemical Name)****Other US EPA or State Lists**

142-82-5	Heptane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Inventory, 4 Test, 8A PAIR; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 1339; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No
74-98-6	Propane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 1594; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No
108-88-3	Toluene	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Inventory, 8A CAIR; CA PROP.65: Yes; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP: Yes; NJ EHS: Yes - 1866; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
106-97-8	Butane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Inventory; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 0273; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No

**CAS # Hazardous Components (Chemical Name)****International Regulatory Lists**

142-82-5	Heptane	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
74-98-6	Propane	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
108-88-3	Toluene	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
106-97-8	Butane	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes



# SAFETY DATA SHEET

## Disc Brake Quiet

**European Community Hazard Symbol codes:**

**European Community Risk and Safety Phrases:**

No data available.

### Section 16. Other Information

**Revision Date:** 10/02/2014

**Additional Information About This Product:** No data available.

**This Product:**

**Company Policy or**

**Disclaimer:**

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.